



YCOB and YCB - 24 & 36
 YWOB and YWB - 24 & 36

YANKEE Boiler



YCOB24
 (coal-wood-oil)



YWB24

The YANKEE Boiler allows the homeowner to burn solid fuel with auto switchover to oil.

SPECIFICATIONS:

UNIT SIZE	YCB 24	YCB 36
	YCOB 24	YCOB 36
	YWB 24	YWB 36
	YWOB 24	YWOB 36
HEAT EXCHANGER		
BTU/H Wood	70,000	100,000
BTU/H Coal	100,000	175,000
Grate Surface (sq. ft.)	2.95	4.43
Net Coal Capacity (lbs.)	150	220
Net Wood Capacity (lbs.)	95	145
Firing Rate GPH #2 Oil	.65	.65
BTU Oil	73,000	73,000
Wood Length	24"	36"
Water Capacity (Gal)	25	35
Supply Tapping (1)	1 1/2"	1 1/2"
Return Tapping (1)	1 1/2"	1 1/2"
Tankless Coil Capacity (gal)	2*	2*
Tankless Coil Tapping (2)	1/2"	1/2"
Cabinet Width	22 1/4"	22 1/4"
Cabinet Length	30 1/2"	42 1/2"
Cabinet Height	45 3/4"	45 3/4"
Firing Door Size (h x w)	11" x 15"	11" x 15"
Stack Diameter	7"	7"
Stack Center from floor	35"	35"
Shipping weight (lbs)	725	930

The YANKEE Boiler

- Large Fuel Capacity
- Large Firedoor for Easy Solid Fuel Loading
- Choice of Wood or Coal Grates
- Convenient Ash Removal
- Solid Fuel and Oil Fires Automatically Controlled to Maintain Water Temperature
- Quiet Efficient Flame Retention Oil Burner
- Attractive "Warm Red" Cabinet
- 5-Year "Limited Warranty"
- Heavy, 1/4" steel plate design.
- Water Filled Tubes Extend Heating Surface
- ASME pressure Relief Valve
- Fusible Plug for Safety
- Coal Units with external shaker handle and Extra Heavy Cast Iron Shaker Grates
- Wood Units with Heavy Cast Iron Tubular Grates
- **Closed Pressurized System**
- American Made

See Add-on Boiler literature for connecting YANKEE Boiler in parallel with existing oil or gas boiler.

* Coil is to be used as a preheater to another heater and is NOT RATED.

Safety tested by an independent laboratory to the following standards: UL391, CSA B 366.1 and ETLM 78-1